

# metalfire

| architectural fireplaces |

**model** URBAN MF 1050-75 G 2S L

**Dimensions (mm)**

- combustion chamber WxDxH 1050 x 370 x 750
- length of burner 800
- external WxDxH 1260 x 425 x 2025
- fresh air 2 x Ø150

**Technical Data (city gas)**

for other types of gas see 'gasburner specifications' (options)

- appliance type B11AS/B14AS
- load 13,9 kW
- type of gas/pressure G20/20,25/25mBar
- gascat. I2E+, I2H, I2E, I2L
- weight +/- 146kg

**Protection**

- 'oxy-pilot'-protection
- ionization-protected pilot-flame
- secured flue pipe discharge
- secured oxygen supply

**Specifications**


- control unit on the right
- finishing: heat-resistant black paint
- lockable valve for fresh air and smoke gases
- grey pebbles
- remote control with electronic ignition
- heat-resistant glass panel height 250mm

**Options**

- chimney fan RSVG 250
- back and side combustion chamber finishing: ribbed cast-iron
- ceramic woodlogs
- convection jacket (see options)

scale 1:20

[www.metalfire.eu](http://www.metalfire.eu)

EN 509 

General dimensional tolerances up to 6mm  
Metalfire preserves the right to modify specifications without previous notice

